

Claims

1. An earthquake prediction method wherein:
telluric current induction fields and telluric currents are
estimated based on magnetic fields that are observed at each point within an
observation area; and
5 change over time of the telluric currents and a state of telluric
currents within said observation area are analyzed to estimate a seismofocal
zone, time of occurrence, and seismic intensity of a seismic event.
2. An earthquake prediction method according to claim 1,
wherein:
a magnetic field noise component at observation points is
eliminated from observed magnetic fields;
5 an amount of divergence of a direction of a magnetic fields
from a direction of true north at observation points from which said magnetic
field noise component has been eliminated is found; and
said telluric current induction fields are estimated based on
vector differences between observed magnetic fields from which said
10 magnetic field noise component has been eliminated and a geomagnetic
vector that has been corrected to true north.
3. An earthquake prediction method according to claim 1 or 2,
wherein:
said estimated telluric current induction fields are plotted on a
map; and

5 said telluric currents are estimated by both joining points on the map at which geomagnetic abnormalities are recognized and applying right-handed screw rule.

4. An earthquake prediction method according to claim 1 or 2 or 3, wherein:

 an area in which said estimated telluric currents are concentrated is estimated to be a seismofocal zone.

5. An earthquake prediction method according to claim 1 or 2, wherein:

 past data of telluric current induction field intensities at specific observation points are gathered and a telluric current induction field intensity
5 change pattern that indicates change over time is generated; and

 this pattern is then compared and collated with past telluric current induction field intensity change patterns that have been stored to estimate said time of occurrence and seismic intensity of a seismic event.

6. An earthquake prediction system comprising:
 mobile units such as vehicles or ships, each unit carrying:
 a magnetic force line sensor for supplying as output magnetic
field data that indicate a direction and intensity of lines of magnetic force;
5 a GPS position detector for receiving radio waves of a GPS
satellite and supplying as output position data that indicate position; and
 a data transmitter for transmitting said data; and

an earthquake prediction center for collecting said data of various points that are transmitted by said mobile units that travel within an observation area and then implementing earthquake prediction.

7. An earthquake prediction system according to claim 6, said earthquake prediction center comprising:

- a data receiver for receiving data that have been transmitted from said mobile units by way of a communication network and antenna;
- 5 a data storage unit for retaining and storing various data such as map data and data that have been received by said data receiver;
- a telluric current induction field estimation unit for estimating telluric current induction fields based on map data and data that have been retained and stored in said data storage unit;
- 10 telluric current estimation unit for estimating telluric currents based on said telluric current induction fields that have been estimated;
- a telluric current induction field intensity change pattern generation unit for accumulating transitions over time of said telluric current induction field intensities and then generating change patterns; and
- 15 an earthquake prediction unit for analyzing said telluric currents that have been estimated and said change patterns of said telluric current induction field intensities to estimate a seismofocal zone, seismic intensity, and time of occurrence of a seismic event.

8. An earthquake prediction system according to claim 6, wherein, when said mobile unit is provided with a car navigation system, position data

of said car navigation system is used instead of data from said GPS position detector.

9. An earthquake prediction system according to claim 6,
wherein:

said magnetic force line sensor and communication equipment
are installed in preselected existing fixed structures within the observation
5 area; and

said communication equipment transmits magnetic field data
output of said magnetic force line sensor and information indicating
installation positions to said earthquake prediction center by way of an
existing communication network.

10. An earthquake prediction system according to claim 6,
wherein:

said magnetic force line sensor and GPS position detector are
incorporated in a mobile telephone or a mobile unit; and

5 said mobile telephone uses its own communication capabilities
to transmit observation data to said earthquake prediction center.

11. An earthquake prediction system according to claim 9, wherein
an acceleration sensor is provided, and said magnetic field data are
transmitted when said acceleration sensor detects earthquake motion.

12. An earthquake prediction system according to claim 6 or 10,
wherein an acceleration sensor is provided and said magnetic field data are

transmitted when said acceleration sensor detects a stationary state of at least a fixed time interval.

5